SBH100/150/200/250/300/350/400

High Voltage LFP Battery

HIGH POWER

- Up to 50A continuous charging and discharging current, 8 modules unit power up to 28 kW
- Up to 100 % usable energy

SAFETY

- Lithium iron phosphate Battery
- Multi-stages protection design and extensive safety certification

FLEXIBILITY

- Extendable during lifetime
- 10–40 kWh capacity range

EASY INSTALLATION

- Plug and play, no cable needed between battery modules

© 2023 Sungrow Power Supply Co., Ltd. All rights reserved. Subject to change without notice. Version 3.1

SUNGROW
Clean power for all

Type designation	SBH100	SBH150	SBH200	SBH250	SBH300	SBH350	SBH400
Technical properties	2 modules	3 modules	4 modules	5 modules	6 modules	7 modules	 8 modules
System data							
Battery type	LiFePO4 Prismatic Cell						
Battery module	5.0 kWh , 45 kg						
Energy (useable) *	10.0 kWh	15.0 kWh	20.0 kWh	25.0 kWh	30.0 kWh	35.0 kWh	40.0 kWh
Nominal voltage	140.8 V	211.2 V	281.6 V	352.0 V	422.4 V	492.8 V	563.2 V
Rated DC power	7.04 kW	10.56 kW	14.08 kW	17.60 kW	21.12 kW	24.64 kW	28.16 kW
Operating voltage	118.8V-160.6V	178.2V-240.9V	237.6V-321.2V	297V-401.5V	356.4V-481.8V	415.8V-562.1V	475.2V-642.4V
Max. charging/discharging current: continuous	50 A						
Depth of discharge	Max. 100 % DOD (settable)						
Short circuit current	3500 A						
Display	SOC indicator , Status indicator						
Communication interface	CAN						
Protection							
Over/under voltage protection	Yes						
Over current protection	Yes						
Over/under temperature protection	Yes						
DC breaker	Yes						
General data							
Dimensions (W*H*D)	675 * 580 * 350 mm	675 * 740 * 350 mm	675 * 900 * 350 mm	675 * 1060 * 350 mm	675 * 1220 * 350 mm	675 * 1380 * 350 mm	675 * 1540 * 350 mm
Weight	106 kg	151 kg	196 kg	241 kg	286 kg	331 kg	376 kg
Installation location	Indoor / Outdoor						
Mounting method	Floor stand						
Operating ambient temperature range	Charge：0 ℃ - 50 ℃ Discharge：-20 ℃ - 50 ℃						
Degree of protection	IP55						
Allowable relative humidity range	0 % - 95 % no condensing						
Max. operating altitude	Max. 2000 m						
Cooling method	Natural convection						
Certificates	CE, CEC, IEC 62619, IEC 62040, UN 38.3, VDE 2510-50, IEC 62477, IEC 63056						
Warranty**	10 Years						

* Test conditions: 25 ℃ , 100 % depth of discharge (DOD), 0.2C charge&discharge
** Refer to battery warranty letter for conditional application

© 2023 Sungrow Power Supply Co., Ltd. All rights reserved. Subject to change without notice. Version 3.1